

RFID CARD READER – RDORE07



FEATURES

- Support card type: EM/ID card(125Khz), IC/Mifare card for options.
- Huge storage capacity, can read 2000 user cards.
- Management card can add or delete user cards easily, simple and convenient operation.
- WG26 input, support external card reader also used as a standalone access controller.
- NO/NC alternative, meet different areas security system condition.
- Narrow frame design, can install on narrow door frame, more widespread application.

MODEL

RD0RE07: RFID card Reader

SPECIFICATION	
Opening Mode	Card
Card type (alternative)	EM,ID card (IC, Mifare card for options)
Wiegand Signal	Wiegand input, Muti-function device, Support external wg26 card reader.
Storage	2000 user cards
Access Control Interface for	3rd party electric lock, exit button, door sensor
Card reading distance	1-15CM
Operating voltage	DC 12V±10%
Operating current	< 100mA
Dimensions	110mm×50mm×20mm
Management	With management card to add/delete card
Waterproof	Conforms to IP54
Dimensions	110*50*20mm
Ambient temperature	0°C - 60°C
Relative humidity	20%—80%
Gross Weight	0.15kg

e-mail : info@radiantsolaris.com

©Copyright 2019. Radiant Solaris Ltd. Radiant[™] Logo is registered trademark of Radiant or a releated companies.

All specifications are subject to change withour notice. All rights reserved.